

1024. *Chevrons, Badges, etc.—How worn.*—Chevrons, G.C. Badges, etc., are to be sewn on at Headquarters strictly in accordance with sealed patterns. The following instructions are for guidance of Inspecting Officers, and Officers and N.C. Officers serving afloat.

Chevrons will be sewn on so as to allow a distance of one inch between outer edges of cloth and the seams of the sleeve.

G.C. Badges as above ; the distance to be $\frac{1}{2}$ inch.

The vertical position to be :—

(a) *Chevrons worn above the elbow.*—The bottom point of chevron to be $10\frac{1}{2}$ inches from point of shoulder.

(b) *Chevrons worn below the elbow and G.C. Badges* :—

(i) Garments without a cuff or braid.—The inner angle of chevron or badge to be 7 inches from bottom of sleeve.

(ii) Garments with round cuff or slash.—The lowest point of chevron or badge to be approximately $\frac{1}{4}$ inch from top of cuff or slash.

(iii) Garments with plain pointed cuff.—Inner angle of chevron or badge to be approximately $\frac{1}{4}$ inch from point of cuff.

(iv) Garments, sleeve ornamented with braid.—Bottom of chevron or badge to be $\frac{1}{8}$ inch clear from sides of knot.

N.B.—In cases where men require very broad or very narrow sleeves, these distances may be varied but the above instructions are to be adhered to as nearly as possible.

All chevrons and G.C. badges are to be sewn on, except in case of Khaki Drill Tunic, when it is to be fastened by hooks and eyes.

(c) *Distinguishing Badges worn on Left Forearm.*—Will be worn in the following order commencing at the bottom :—

Crossed Rifles.

Naval Gunnery Badge.

Land Service Gunnery Badge.

Crossed Flags.

CLOTHING, DRESS, EQUIPMENT, AND STORES:

A $\frac{1}{4}$ -in. to be left clear between point of cuff, top of knot or G.C. Badge (7 inches, when no cuff or G.C. Badge, from bottom of sleeve) respectively and between each badge.